



Donaldson.
FILTRATION SOLUTIONS


PRODUCT PROFILE

STEPPED SEALCLAMP™ EXHAUST CLAMP


Fewer Parts, Lighter Weight and Easier to Install

Three Simple Installation Steps

1 Position the SealClamp over the smallest tube. Larger end of the clamp must be on the overlapping tube or flex.




2 Locate the step of the clamp to the overlapping tube at the joint.



3 Using the groove as a visual guide, alternately tighten bolts until the groove is approximately half closed (~50 ft. lbs).

open



closed



Note: Do not exceed 70 ft. lbs. torque as clamp damage may occur.

Used to seal muffler inlets, outlets, elbow joints, flex pipes, and other system connections. Also minimizes noise and exhaust gas leaks. SealClamps are easy to install! There's no need to weld or disconnect your exhaust system. When installed, the wide band conforms to the shape of straight or flex pipe, and seals without distorting the pipe.

Easier to install

- ▶ Pre-assembled with fewer parts
- ▶ Requires less torque than other designs
- ▶ One wrench installation
- ▶ Reversible threaded nut bar

Visual torque indicator

- ▶ Lower torque makes for easier and quicker installation
- ▶ Groove provides a visual guide to correct torque



360° stepped shape improves joint seal

- ▶ Reduces exhaust leaks by more than 65% compared to other non-gasketed clamp designs
- ▶ Resistance to joint separation is nearly twice that of other brands
- ▶ Conforms tightly to overlapping connections – ideal for most overlapping I.D. to O.D. joints
- ▶ Reduced flex pipe pinching
- ▶ Reduces exhaust noise

Quality materials

- ▶ 0.064-0.090Kg lighter than other brands
- ▶ Improved rust resistance
- ▶ Available in stainless with aluminum and zinc-plated components
- ▶ High strength, grade 8 fasteners



Order Information		
O.D. Pipe		Part No.
inches	mm	Stainless
2.50	64	X007829
3.00	76	X007830
3.50	89	X007831
4.00	102	X007784
5.00	127	X007785*
6.00	152	X009076

* Also available as a bulk pack of 48 clamps (part number X007785-48)



Stepped Preformed SealClamp is individually packaged with installation instructions.

Donaldson Australasia Pty Ltd
PO Box 153, Wyong NSW 2259

Free call: 1800 345 837
Ph: +61 2 4350 2000
Fax: +61 2 4351 2036

Donaldson New Zealand
PO Box 14-770, Panmure 1741 Auckland

Ph: +64 9 579 2790
Fax: +64 9 579 0322

Product Profile No. 10PP003 (11/10)

© 2010 Donaldson Company, Inc. All rights reserved. Printed in Australia. Donaldson reserves the right to change or discontinue any model or specification at any time and without notice.

www.donaldsonfilters.com.au