

Deutsche Keilriemen GmbH

Corveyer Allee 15 • 37671 Höxter, Germany
Phone +49 (0) 52 71 - 6 21 • Fax +49 (0) 52 71 - 97 62 00
info@optibelt.com • http://www.optibelt.com



Certificate of Compliance in accordance with EN 10204 – 2.1 for antistatic V-belts, joined V-belts and timing belts*

We hereby confirm to Optibelt GmbH, Höxter, that the Optibelt V-belts and joined V-belts as well as the Optibelt timing belts listed below and marked accordingly meet the requirements of electrical conductivity in accordance with ISO 1813 for V-belts and joined V-belts as well as ISO 9563 for timing belts at the time of delivery. This Certificate of Compliance shall only apply to Optibelt joined V-belts for drives with inside located pulleys and expressly not for drives with additional external rollers since the cover plate in the standard version is not antistatic. In addition to the standard version, this Certificate of Compliance also refers to further design variations, but not to the above mentioned special versions.

V-belts and related joined V-belts (if available)

Optibelt VB without versions 84, 85 and without VB-LC
Optibelt SK without versions 84, 85
Optibelt Red Power 3
Optibelt Blue Power
Optibelt HVAC Power
Optibelt LD without versions 84, 85
Optibelt DK
Optibelt Super TX
Optibelt Super X-Power
Optibelt VS
Optibelt Vario Power

with the marking

Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813
Antistatic ISO 1813

Timing belts

Optibelt Omega HP, profiles 8M and 14M
Optibelt Omega HL, profiles 8M and 14M
Optibelt Omega Fan Power, profiles 8M and 14M

with the marking

Antistatic ISO 9563
Antistatic ISO 9563
Antistatic ISO 9563

Höxter, 15.08.2012

Konrad Ummen

Reinhold Mühlbeyer

*Note: When in use, the resistance values of drive components can change substantially. For this reason, the respective user shall ensure by way of appropriate measures that the drive components will be able to accomplish their function of discharging electrical charges during their entire working life.